Amendment to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1 (currently amended) A light emitting GaN based device, comprising:
a semiconductor device that emits light having a wavelength in the range of 200 nm to 620 nm; and

a blue phosphor; and

a red phosphor having the formula:

where x is greater than 0 and less than 1, Ln is an element selected from the group consisting of Y, La and Gd, and A is an activator selected from Eu³⁺, Sm³⁺ and Pr³⁺, or any combination thereof, with or without Tb³⁺ as a co-dopant.

2 (original) The device of claim 1 in which the red phosphor absorbs light of a wavelength in the range of 240 nm to 550 nm and emits red light at a wavelength in the range of 580 nm to 700 nm.

- 3 (canceled)
- 4 (canceled)
- 5 (currently amended) The device of claim 30 in which said red phosphor has the formula:

where x = 0 to 1, Ln is an element selected from the group consisting of Y, La and Gd, and A is an Tb^{3+} and at least one activator selected from Eu^{3+} , Sm^{3+} and Pr^{3+} , or any combination thereof.

25557463.1 -2-

6 (original) The device of claim 5 in which x is greater than 0 and less than 1.

7 (original) The device of claim 6 in which x is 0.05 to 0.5.

8 (canceled)

9 (previously presented) The device of claim 29 in which the semiconductor device is a GaN based device.

10 (original) The device of claim 1 in which the semiconductor device is a vertical cavity surface emitting laser, a light emitting diode, or a laser diode.

11 (previously presented) The device of claim 29 in which the semiconductor device is a GaN based device.

12 (original) The device of claim 11 in which the semiconductor device is a light emitting diode.

13 (canceled)

14 (original) A light emitting semiconductor device, comprising:

a GaN based light emitting diode that emits light having a wavelength in the range of 200 nm to 620 nm;

a red phosphor that absorbs light of a wavelength in the range of 240 nm to 550 nm and emits red light at a wavelength in the range of 580 nm to 700 nm, having the formula:

where x is 0.05 to 0.5, Ln is an element selected from the group consisting of Y, La and Gd, and A is an activator selected from Eu^{3+} , Sm^{3+} and Pr^{3+} , or any combination thereof, with or without Tb^{3+} as a co-dopant;

a green phosphor; and

a blue phosphor.

15 (original) The device of claim 14 including Tb³⁺ as a co-dopant.

25557463.1 -3-

- 16 (previously presented) The device of claim 14 in which said green phosphor is ZnS:(Cu⁺,Al³⁺) and said blue phosphor is BaMgAl₁₀O₁₇:Eu²⁺.
 - 17 (previously presented) A white light emitting phosphor combination, comprising: a red phosphor having the formula:

$$Bi_xLn_{1-x}VO_4:A$$

where x is greater than 0 and less than 1, Ln is an element selected from the group consisting of Y, La and Gd, and A is an activator selected from-Eu³⁺, Sm³⁺ or Pr³⁺, or any combination thereof, with or without Tb³⁺ as a co-dopant;

- a green phosphor; and
 - a blue phosphor.
- 18 (original) The phosphor combination of claim 17 in which said red phosphor absorbs light of a wavelength in the range of 240 nm to 550 nm and emits red light at a wavelength in the range of 580 nm to 700 nm.
- 19 (currently amended) The phosphor combination of claim 31 in which said red phosphor has the formula:

where x = 0 to 1, Ln is an element selected from the group consisting of Y, La and Gd, and A is an \underline{Tb}^{3+} and at least one activator selected from Eu^{3+} , Sm^{3+} and Pr^{3+} , or any combination thereof, with or without Tb^{3+} as a co-dopant.

- 20 (original) The phosphor combination of claim 19 in which x is greater than 0 and less than 1.
 - 21 (original) The phosphor combination of claim 20 in which x is 0.05 to 0.5.
 - 22 (canceled)
- 23 (previously presented) The phosphor combination of claim 17 in which said green phosphor is ZnS:(Cu⁺,Al³⁺) and said blue phosphor is BaMgAl₁₀O₁₇:Eu²⁺ suitable for use in a GaN based device..

25557463.1 -4

24 (previously presented) A white light emitting phosphor combination,

a red phosphor that absorbs said light of a wavelength in the range of 240 nm to 550 nm and emits red light at a wavelength in the range of 580 nm to 700 nm, having the formula:

where x is 0.05 to 0.5, Ln is an element selected from the group consisting of Y, La and Gd, and A is an activator selected from Eu^{3+} , Sm^{3+} and Pr^{3+} , or any combination thereof, with or without Tb^{3+} as a co-dopant.;

a green phosphor comprising ZnS:(Cu⁺,Al³⁺); and a blue phosphor comprising BaMgAl₁₀O₁₇:Eu²⁺.

25 (original) The phosphor combination of claim 24 in which said red phosphor includes Tb³⁺ as a co-dopant.

26 (previously presented) A red phosphor that absorbs said light of a wavelength in the range of 240 nm to 550 nm and emits red light at a wavelength in the range of 580 nm to 700 nm, having the formula:

where x is 0.05 to 0.5, Ln is an element selected from the group consisting of Y, La and Gd, and A is an activator selected from Eu^{3+} , Sm^{3+} and Pr^{3+} , or any combination thereof, with or without Tb^{3+} as a co-dopant.

27 (currently amended) The phosphor of claim 32 in which x is 0.05 to 0.5.

28 (currently amended) The phosphor of claim 26 in which in which said red phosphor includes Tb³⁺ as a co-dopant.

29 (previously presented) A light emitting device, comprising:

a semiconductor device that emits light having a wavelength in the range of 200 nm to 620 nm; and

a red phosphor having the formula:

$$Bi_xLn_{1-x}VO_4:A$$

-5-

where x is 0.05 to 0.5, Ln is an element selected from the group consisting of Y, La and Gd, and A is an activator selected from Eu^{3+} , Sm^{3+} and Pr^{3+} , or any combination thereof, with or without Tb^{3+} as a co-dopant.

30 (previously presented) A light emitting device, comprising:

a semiconductor device that emits light having a wavelength in the range of 200 nm to 620 nm; and

a red phosphor comprising a vanadate combined with yttrium, gadolinium and/or lanthanum and activated with trivalent Eu³⁺, Sm³⁺ or Pr³⁺, or any combination thereof, with Tb³⁺ as a co-dopant.

31 (previously presented) A white light emitting phosphor combination, comprising: a red phosphor comprising a vanadate combined with yttrium, gadolinium and/or lanthanum and activated with trivalent Eu³⁺, Sm³⁺ and Pr³⁺, or any combination thereof, with Tb³⁺ as a co-dopant;

a green phosphor; and a blue phosphor.

32 (previously presented) A red phosphor that absorbs said light of a wavelength in the range of 240 nm to 550 nm and emits red light at a wavelength in the range of 580 nm to 700 nm, having the formula:

where x is greater than 0 and less than 1, Ln is an element selected from the group consisting of Y, La and Gd, and A is an activator selected from Eu^{3+} , Sm^{3+} and Pr^{3+} , or any combination thereof, with Tb^{3+} as a co-dopant.

33 (new) A light emitting GaN based device, comprising:

a semiconductor device that emits light having a wavelength in the range of 200 nm to 620 nm;

a green phosphor and a blue phosphor; and a red phosphor having the formula:

25557463.1 -6-

$Bi_xLn_{1-x}VO_4:A$

where x is greater than 0 and less than 1, Ln is an element selected from the group consisting of Y, La and Gd, and A is an activator selected from Eu³⁺, Sm³⁺ and Pr³⁺, or any combination thereof, with or without Tb³⁺ as a co-dopant.

34 (new) A light emitting GaN based device, comprising:
a semiconductor device that emits light having a wavelength in the range of 200 nm to 620 nm;

a red phosphor having the formula:

$$Bi_xLn_{1-x}VO_4:A$$

where x is greater than 0 and less than 1, Ln is an element selected from the group consisting of Y, La and Gd, and A is an activator selected from Eu³⁺, Sm³⁺ and Pr³⁺, or any combination thereof, with or without Tb³⁺ as a co-dopant;

a green phosphor having the formula: $ZnS:(Cu^{+},Al^{3+})$; and a blue phosphor having the formula: $BaMgAl_{10}O_{17}:Eu^{2+}$.